



Putty Pads For Drywall Socket Boxes

are you in the *know*?

KNAUF DRYWALL

Putty Pads

Knauf Putty Pads are sheets of intumescent, mouldable putty designed for use inside and outside plastic electrical socket boxes. They offer not only fire protection but also ensure that the acoustic integrity of a system is maintained, without the need for baffle boxes.

Fire and Acoustic Protection of drywall socket boxes is made simple by using new Knauf Putty Pads.

Knauf Putty Pads are:

- Quick and easy to install
- Designed to fit most typical drywall socket boxes
- Suitable for use in all applications e.g. residential, commercial, etc.

Knauf Putty Pads will maintain a fire rating of up to 2 hours in drywall applications and an acoustic rating of up to 60dB Rw.

Two Sizes of Putty Pads are available:

180mm x 130mm - Article code: 736 25 300

230mm x 230mm - Article code: 736 25 301

Both are 3.5mm thick and come in boxes of 20.

Knauf Putty Pads are supplied with an easy to peel paper on both sides of the pad.

Knauf Putty Pad Performance Information	
Application temperature	0°C – 50°C
Storage temperature	10°C – 30°C
Cure	Non-setting
pH	Neutral
Intumescent activation	Approx. 200°C

Customer Service

Freephone: 0800 521 050

Freefax: 0800 521 205

email: cservice@knauf.co.uk

Technical Service Hotline:

01795 416 259

Website

www.knaufdrywall.co.uk/themanual

Knauf Drywall

PO Box 133


Sittingbourne Kent ME10 3HW

Installation Guide:

(Inside Fitting)

Always wear protective gloves when handling

1. Remove the paper from one side of the pad.



2. Make a slit for the cable and pass the cable through the pad.



3. Push the pad fully inside the box.



4. Pay special attention to the corners.



5. Trim off any excess material.

